SERIES

62AL

"TR-ROLL" POLYURETHANE WHEELS WITH ALUMINIUM CENTRE

Heavy-duty PT brackets with hardened ball race grooves - max carrying capacity 700 daN



1) Top Plate: electrolytically galvanised steel plate
2) Fork: electrolytically galvanised steel plate
3) Ball Race Ring: electrolytically galvanised steel plate
4) Dust Seal: dark green polyamide 6
5) Swivel actions: double ball ring with grease lubrication
6) Ball race: hardened carbon steel grooves
7) King pin: steel screw, class 8.8 and stainless steel nut
Available with rear adjustable brake

														4 km/h	6 km/h
mm	mm	kg	COD.	kg	COD.	kg	COD.	mm	mm	mm	mm	mm	mm	daN	daN
125	40	2,33	625003	1,69	628503	2,86	629903	170	140x110	105x80	11	70	126	**350**	**350**
160	50	3,52	625010	2,11	628514	4,12	629904	205	140x110	105x80	11	70	126	**550**	**550**
180	50	3,91	625005	2,42	628515	4,38	629905	228	140x110	105x80	11	70	126	**600**	**600**
200	50	4,10	625016	2,85	628516	4,66	629906	250	140x110	105x80	11	70	126	**700**	**700**

SERIES

62ER

"TR-ROLL" POLYURETHANE WHEELS WITH ERGONOMIC ROUND PROFILE WITH ALUMINIUM CENTRE

Heavy-duty PT brackets with hardened ball race grooves - max carrying capacity 700 daN



1) Top Plate: electrolytically galvanised steel plate
2) Fork: electrolytically galvanised steel plate
3) Ball Race Ring: electrolytically galvanised steel plate
4) Dust Seal: dark green polyamide 6
5) Swivel actions: double ball ring with grease lubrication
6) Ball race: hardened carbon steel grooves
7) King pin: steel screw, class 8.8 and stainless steel nut
Available with rear adjustable brake

														4 km/h	6 km/h
mm	mm	kg	COD.	kg	COD.	kg	COD.	mm	mm	mm	mm	mm	mm	daN	daN
125	50	2,42	629033	1,96	629113	2,95	629233	170	140x110	105x80	11	70	126	**450**	**400**
160	50	3,52	629034	2,28	629104	4,12	629234	205	140x110	105x80	11	70	126	**550**	**550**
200	50	4,10	629036	2,68	629106	4,66	629236	250	140x110	105x80	11	70	126	**700**	**700**

SERIES

62GH

"TR-ROLL" POLYURETHANE WHEELS WITH CAST IRON CENTRE

Heavy-duty PT brackets with hardened ball race grooves - max carrying capacity 900 daN



1) Top Plate: electrolytically galvanised steel plate
2) Fork: electrolytically galvanised steel plate
3) Ball Race Ring: electrolytically galvanised steel plate
4) Dust Seal: dark green polyamide 6
5) Swivel actions: double ball ring with grease lubrication
6) Ball race: hardened carbon steel grooves
7) King pin: steel screw, class 8.8 and stainless steel nut
Available with rear adjustable brake

mm	mm	kg	COD.	kg	COD.	kg	COD.	mm	mm	mm	mm	mm	mm	4 km/h daN	6 km/h daN
200	50	5,80	627646	5,42	628656	6,35	627246	250	140x110	105x80	11	70	126	**800**	**800**

SERIES

63AC

VULKOLLAN® WHEELS WITH FORGED STEEL CENTRE

Heavy-duty PT brackets with hardened ball race grooves - max carrying capacity 900 daN



1) Top Plate: electrolytically galvanised steel plate
2) Fork: electrolytically galvanised steel plate
3) Ball Race Ring: electrolytically galvanised steel plate
4) Dust Seal: dark green polyamide 6
5) Swivel actions: double ball ring with grease lubrication
6) Ball race: hardened carbon steel grooves
7) King pin: steel screw, class 8.8 and stainless steel nut
Available with rear adjustable brake

mm	mm	kg	COD.	kg	COD.	kg	COD.	mm	mm	mm	mm	mm	mm	4 km/h daN	6 km/h daN
150	40	4,19	635604	2,70	638624	4,76	635304	200	140x110	105x80	11	70	126	**750**	**600**
175	40	5,14	635605	3,72	638625	5,71	635305	225	140x110	105x80	11	70	126	**850**	**680**
200	50	6,44	635606	4,98	638626	7,01	635306	250	140x110	105x80	11	70	126	**900**	**800**

SERIES

63GH

VULKOLLAN® WHEELS WITH CAST IRON CENTRE

Heavy-duty PT brackets with hardened ball race grooves - max carrying capacity 900 daN



1) Top Plate: electrolytically galvanised steel plate
2) Fork: electrolytically galvanised steel plate
3) Ball Race Ring: electrolytically galvanised steel plate
4) Dust Seal: dark green polyamide 6
5) Swivel actions: double ball ring with grease lubrication
6) Ball race: hardened carbon steel grooves
7) King pin: steel screw, class 8.8 and stainless steel nut
Available with rear adjustable brake

		kg		kg		kg									4 km/h	6 km/h
mm	mm	kg	COD.	kg	COD.	kg	COD.	mm	mm	mm	mm	mm	mm	daN	daN
125	50	3,66	635003	2,65	636863	4,24	639903	170	140x110	105x80	11	70	126	**600**	**440**
150	50	4,81	635004	3,55	636854	5,33	639904	200	140x110	105x80	11	70	126	**700**	**560**
160	50	4,93	635014	4,08	636864	5,45	639914	205	140x110	105x80	11	70	126	**750**	**600**
180	50	5,30	635005	4,45	636855	5,90	639905	228	140x110	105x80	11	70	126	**900**	**720**
200	50	6,06	635006	5,15	636856	6,66	639906	250	140x110	105x80	11	70	126	**900**	**800**

SERIES

64

"TR" POLYURETHANE WHEELS WITH CAST IRON CENTRE

Heavy-duty PT brackets with hardened ball race grooves - max carrying capacity 900 daN



1) Top Plate: electrolytically galvanised steel plate
2) Fork: electrolytically galvanised steel plate
3) Ball Race Ring: electrolytically galvanised steel plate
4) Dust Seal: dark green polyamide 6
5) Swivel actions: double ball ring with grease lubrication
6) Ball race: hardened carbon steel grooves
7) King pin: steel screw, class 8.8 and stainless steel nut
Available with rear adjustable brake

		kg		kg		kg									4 km/h	6 km/h
mm	mm	kg	COD.	kg	COD.	kg	COD.	mm	mm	mm	mm	mm	mm	daN	daN
125	50	3,66	645003	2,65	646863	4,24	649903	170	140x110	105x80	11	70	126	**550**	**440**
150	50	4,67	645004	3,55	646854	5,33	649904	200	140x110	105x80	11	70	126	**700**	**560**
160	50	4,93	645014	4,08	646864	5,45	649914	205	140x110	105x80	11	70	126	**750**	**600**
180	50	5,30	645005	4,45	646855	5,90	649905	228	140x110	105x80	11	70	126	**900**	**720**
200	50	6,06	645006	5,15	646856	6,66	649906	250	140x110	105x80	11	70	126	**900**	**800**

SERIES

65AL

"TR" POLYURETHANE WHEELS WITH ALUMINIUM CENTRE

Heavy-duty PT brackets with hardened ball race grooves - max carrying capacity 850 daN



1) Top Plate: electrolytically galvanised steel plate
2) Fork: electrolytically galvanised steel plate
3) Ball Race Ring: electrolytically galvanised steel plate
4) Dust Seal: dark green polyamide 6
5) Swivel actions: double ball ring with grease lubrication
6) Ball race: hardened carbon steel grooves
7) King pin: steel screw, class 8.8 and stainless steel nut
Available with rear adjustable brake

		kg		kg		kg									4 km/h	6 km/h
mm	mm	kg	COD.	kg	COD.	kg	COD.	mm	mm	mm	mm	mm	mm	daN	daN
150	50	3,18	657544	2,19	658604	3,66	656674	200	140x110	105x80	11	70	126	**600**	**480**
160	50	3,52	657554	2,53	658614	4,09	656684	205	140x110	105x80	11	70	126	**800**	**640**
200	50	3,94	657546	2,48	658606	4,41	656676	250	140x110	105x80	11	70	126	**850**	**680**

SERIES

65GH

"TR" POLYURETHANE WHEELS WITH CAST IRON CENTRE

Heavy-duty PT brackets with hardened ball race grooves - max carrying capacity 900 daN



1) Top Plate: electrolytically galvanised steel plate
2) Fork: electrolytically galvanised steel plate
3) Ball Race Ring: electrolytically galvanised steel plate
4) Dust Seal: dark green polyamide 6
5) Swivel actions: double ball ring with grease lubrication
6) Ball race: hardened carbon steel grooves
7) King pin: steel screw, class 8.8 and stainless steel nut
Available with rear adjustable brake

		kg		kg		kg									4 km/h	6 km/h
mm	mm	kg	COD.	kg	COD.	kg	COD.	mm	mm	mm	mm	mm	mm	daN	daN
150	35	3,95	657444	2,51	658414	4,52	658314	200	140x110	105x80	11	70	126	**490**	**390**
175	35	4,42	657435	3,00	658405	4,99	658305	225	140x110	105x80	11	70	126	**650**	**520**
200	45	5,89	657436	4,43	658406	6,20	658306	250	140x110	105x80	11	70	126	**900**	**800**

SERIES

65HE

WHEELS WITH THICK "TR" POLYURETHANE AND ALUMINIUM CENTRE

Heavy-duty PT brackets with hardened ball race grooves - max carrying capacity 800 daN



1) Top Plate: electrolytically galvanised steel plate
2) Fork: electrolytically galvanised steel plate
3) Ball Race Ring: electrolytically galvanised steel plate
4) Dust Seal: dark green polyamide 6
5) Swivel actions: double ball ring with grease lubrication
6) Ball race: hardened carbon steel grooves
7) King pin: steel screw, class 8.8 and stainless steel nut
Available with rear adjustable brake

															4 km/h	6 km/h
mm	mm	kg	COD.	kg	COD.	kg	COD.	mm	mm	mm	mm	mm	mm	daN	daN
125	40	2,30	655333	1,63	655403	2,83	655533	170	140x110	105x80	11	70	126	**450**	**360**
160	50	3,34	655344	2,04	655414	3,97	655544	205	140x110	105x80	11	70	126	**700**	**560**
180	50	3,71	655335	2,36	655415	4,35	655535	228	140x110	105x80	11	70	126	**750**	**600**
200	50	4,36	655336	2,76	655416	4,89	655536	250	140x110	105x80	11	70	126	**800**	**640**

SERIES

65ER

"TR" POLYURETHANE WHEELS WITH ERGONOMIC ROUND PROFILE AND ALUMINIUM CENTRE

Heavy-duty PT brackets with hardened ball race grooves - max carrying capacity 900 daN



1) Top Plate: electrolytically galvanised steel plate
2) Fork: electrolytically galvanised steel plate
3) Ball Race Ring: electrolytically galvanised steel plate
4) Dust Seal: dark green polyamide 6
5) Swivel actions: double ball ring with grease lubrication
6) Ball race: hardened carbon steel grooves
7) King pin: steel screw, class 8.8 and stainless steel nut
Available with rear adjustable brake

															4 km/h	6 km/h
mm	mm	kg	COD.	kg	COD.	kg	COD.	mm	mm	mm	mm	mm	mm	daN	daN
125	40	2,27	655953	1,63	656013	2,83	656353	170	140x110	105x80	11	70	126	**450**	**360**
160	50	3,34	655954	2,28	656014	3,97	656354	205	140x110	105x80	11	70	126	**700**	**560**
200	50	4,36	655956	2,68	656016	4,89	656356	250	140x110	105x80	11	70	126	**800**	**640**

SERIES

72AL

SIGMA ELASTIC RUBBER WHEELS WITH ALUMINIUM CENTRE

Heavy-duty PT brackets with hardened ball race grooves - max carrying capacity 500 daN



1) Top Plate: electrolytically galvanised steel plate
2) Fork: electrolytically galvanised steel plate
3) Ball Race Ring: electrolytically galvanised steel plate
4) Dust Seal: dark green polyamide 6
5) Swivel actions: double ball ring with grease lubrication
6) Ball race: hardened carbon steel grooves
7) King pin: steel screw, class 8.8 and stainless steel nut
Available with rear adjustable brake

		kg		kg		kg									4 km/h	6 km/h
mm	mm	kg	COD.	kg	COD.	kg	COD.	mm	mm	mm	mm	mm	mm	daN	daN
125	50	2,30	725503	1,66	728523	2,86	728203	170	140x110	105x80	11	70	126	**230**	**180**
160	50	3,59	725510	2,08	728514	4,14	728204	205	140x110	105x80	11	70	126	**300**	**240**
180	50	3,90	725505	2,39	728515	4,38	728205	228	140x110	105x80	11	70	126	**350**	**280**
200	50	4,46	725516	3,00	728516	5,03	728206	250	140x110	105x80	11	70	126	**500**	**400**